



THE SPECIALTY MFG. CO.

5858 Centerville Road • St. Paul, MN 55127-6804 Tel: (651) 653-0599 • Fax: (651) 653-0989 www.specialtymfg.com • e-mail: info@specialtymfg.com

038 SERIES BALL VALVE







Design Considerations

The 038 Series Two-Way Ball Valve compact design promotes multiple configurations to fit the exact end use application. The 038 Ball Valve Series is rated to 500 psi and will support flow and pressure in either direction. The 038 Series has a two-piece body and end construction to cover 3/8" NPT end configuration applications. The Zinc Die Cast Lever Handle is standard. Handles can be ordered Reversed - to lie over the outlet when the valve is in the open position. UL configurations are available and rated to 250 psi. UR configurations are available and rated to 500 psi.

Maximum Operating Pressure — 500 psi Maximum Operating Temperature — 180°F Ball Through Hole Diameter — .312

Options

Material Options Brass Body, Nickel Plated Brass Ball, Teflon® Seats, Stainless Handle Screw

Seal Options Buna-N, Ethylene Propylene, Fluoroelastomer (Viton®), Neoprene

End Options 1/4, 3/8 Male and Female NPT

3/8 Compression 3/8 Hose Barb

Body Options 1/4, 3/8 Male NPT

3/8 Female NPT

Handle Options Zinc Die Cast Lever (Standard), Zinc Die Cast Lever with Red Vinyl Sleeve,

Steel Lever Handle, Steel Lever with Red Vinyl Sleeve

Plating Options No Plating (Standard), Electroless Nickel

Example of How To Order

Inlet EndOutlet EndSealHandlePlating3/8 Compression3/8 MNPTBuna-NSteelENP

SMC Part Number: 038-6C6M-B,SH,ENP

The handle will lie over the Inlet port when the valve is in the open position. SMC Part Numbers are a description of the valve as read left to right, Inlet to Outlet.

Example: 038-6C6M-B,SH,ENP = 3/8 Compression Inlet x 3/8 MNPT Outlet