



Vertically Integrated, Made in the USA  
www.specialtymfg.com

## THE SPECIALTY MFG. CO.

5858 Centerville Road  
St. Paul, MN 55127

SMC will quote alternate materials or customize our standard products when quantities ensure competitive pricing.

Contact Customer Service at (651) 653-0599

FAX - (651) 653-0989

E-Mail - info@specialtymfg.com

## SINGLE SHUTOFFS 3/4" GARDEN HOSE



### Design Considerations

- Shutoffs are inexpensive Female Garden Hose to Male Garden Hose valves designed for outdoor use
- Shutoffs are designed for city water pressure to a maximum of 80 psi
- Shutoffs are a one way valve and require approximately 20 psi of water pressure to seal in the closed position
- An optional Zero Pressure Washer is available for #35 and #65 Shutoff applications with less than 20 psi of working line pressure
- Custom Colors are available for orders of 30,000 or more
- The #45 Swivel Shutoff incorporates a Swivel Female Garden Hose Inlet End

### **Example of how to order**

<u>Type</u>	<u>Color</u>	<u>Washer</u>
Single Shutoff	Yellow	Garden Hose Washer

**Part Numbers** are a description of the Shutoff.

**#35 SHUTOFF, YELLOW** = Yellow ABS Single Shutoff, 3/4 Female Garden Hose Inlet x 3/4 Male Garden Hose Outlet, Buna Seals, Black ABS Handle, Garden Hose Washer

### Specifications

<b>Body Type</b>	#35 Single Shutoff #45S Swivel Shutoff #65 Zinc Single Shutoff
<b>Material</b>	ABS - Black ABS - Blue ABS - Green ABS - White ABS - Yellow Zinc - Die Cast Black Glass Filled Polypropylene White Glass Filled Polypropylene
<b>Flow Type</b>	All Shutoffs - Flow from Female to Male
<b>Handle Option</b>	Black ABS Handle and Ball
<b>Seal Option</b>	Buna-N
<b>Washer Option</b>	GARDEN HOSE WASHER - Requires 20 psi to Seal ZERO PRESSURE WASHER - Requires less than 20psi to Seal
<b>Maximum Operating Pressure</b>	80 psi
<b>Maximum Operating Temperature</b>	125 °F
<b>Ball Through Hole Diameter</b>	0.437 in
	It is the sole responsibility of the system designer and user to select products suitable for their

<b>Compatibility Statement</b>	specific application requirements and to ensure proper installation, operation, and maintenance of these products. Material compatibility, product ratings and application details should be considered in the selection. Improper selection or use of products described herein can cause personal injury or product damage.
<b>Pricing and Minimum Order Requirement</b>	Our Minimum Order Requirements are \$100.00 Domestic - \$250.00 International. Pricing is based on the quantity ordered. <b>Please indicate a typical order quantity or Estimated Annual Usage when requesting pricing.</b>