



Vertically Integrated, Made in the USA
www.specialtymfg.com

THE SPECIALTY MFG. CO.

5858 Centerville Road
St. Paul, MN 55127

SMC will quote alternate materials or customize our standard products when quantities ensure competitive pricing.

Contact Customer Service at (651) 653-0599

FAX - (651) 653-0989

E-Mail - info@specialtymfg.com

902 SERIES SWIVEL

1/4" NPT



Design Considerations

- The 902 Swivel promotes a compact design for 1/4 NPT fluid hose and air line applications
- Maximum Operating Pressure - 1000 psi
- Bronze Thrust Bearing for low torque with a Buna-N seal is standard
- Ethylene Propylene and Viton® seals are available

Example of how to order

Type	Inlet	Outlet	Seal
Inline Swivel	1/4 Female NPT	1/4 Male NPT	Viton®

Part Numbers are a description of the swivel as read left to right, Inlet Port to Outlet Port.
SWIVEL 902-4F4M-F = Brass Inline Swivel, 1/4 Female NPT x 1/4 Male NPT, Viton® Seals

Specifications

Material	BODY and ENDS - Brass, THRUST BEARING - Bronze
Body Option	1/4 Female NPT x 1/4 Male NPT 1/4 Male NPT x 1/4 Barb
Seal Option	Buna-N, Ethylene Propylene, Fluoroelastomer (Viton®)
Through Hole Diameter	0.188
Maximum Operating Pressure	1000 psi
Maximum Operating Temperature	180 °F
Compatibility Statement	It is the sole responsibility of the system designer and user to select products suitable for their specific application requirements and to ensure proper installation, operation, and maintenance of these products. Material compatibility, product ratings and application details should be considered in the selection. Improper selection or use of products described herein can cause personal injury or product damage.
Pricing and Minimum Order Requirement	Our Minimum Order Requirements are \$100.00 Domestic - \$250.00 International. Pricing is based on the quantity ordered. Please indicate a typical order quantity or Estimated Annual Usage when requesting pricing.