



Vertically Integrated, Made in the USA
www.specialtymfg.com

THE SPECIALTY MFG. CO.

5858 Centerville Road
St. Paul, MN 55127

SMC will quote alternate materials or customize our standard products when quantities ensure competitive pricing.

Contact Customer Service at (651) 653-0599

FAX - (651) 653-0989

E-Mail - info@specialtymfg.com

M SERIES SWIVEL

10-32

Design Considerations



- Inline Swivel, Low Torque, 10-32 Male or 10-32 Female Ends
- Available with Buna-N, EP or Viton Seals

Example of how to order

<u>Type</u>	<u>Inlet</u>	<u>Outlet</u>	<u>Seal</u>
Inline Swivel	10-32 Female	10-32 Male	Viton®

Part Numbers are a description of the swivel as read left to right, Inlet Port to Outlet Port.
SWIVEL-M-10-32F,10-32M-F= Inline Swivel, 10-32 Female x 10-32 Male, Viton® Seals

Specifications

Material	Electroless Nickel Plated Brass
Body Option	10-32 Female Inlet x 10-32 Male Outlet 10-32 Male Inlet x 10-32 Male Outlet
Seal Option	Buna-N, Ethylene Propylene, Fluoroelastomer (Viton®)
Maximum Operating Pressure	125 psi
Maximum Operating Temperature	180 °F
Cv	.1
Compatibility Statement	It is the sole responsibility of the system designer and user to select products suitable for their specific application requirements and to ensure proper installation, operation, and maintenance of these products. Material compatibility, product ratings and application details should be considered in the selection. Improper selection or use of products described herein can cause personal injury or product damage.
Pricing and Minimum Order Requirement	Our Minimum Order Requirements are \$100.00 Domestic - \$250.00 International. Pricing is based on the quantity ordered. Please indicate a typical order quantity or Estimated Annual Usage when requesting pricing.