Miniature Valves:

<u>Toggle, Push-Button & Needle Valves</u> > <u>PILOT VALVES</u> > MASTER SHUT-OFF ASSEMBLY 10-32, 1/16" to 1/8" BARB

MASTER SHUT-OFF ASSEMBLY 10-32, 1/16" to 1/8" BARB



larger image

Part # 218690 M-PAB2NC-B3/8,10-32F (Kit) (Includes Items Listed Below)

Part # 218890 RG2NO-B1/4-20F NPM (Standard Regulator) Part # 231390 M-PAB2NC-B3/8,1/4-20 (Standard Shut Off Without Regulator)

Available without Regulator 1/4-20 Female Output Flow Rate: 2.5 SCFM @ 50

PORT DEFINITIONS

1. 3/8 Copper Compression Input

2. 10/32 Female
Output-Off of Regulator

3. 10/32 Female
Auxiliary Output

Auxiliary Output (Plugged)

4. 10/32 Female Auxiliary Output (Plugged, Pre-filtered

Port)

5. 10/32 Female Auxiliary Outputs-Off of Regulator (Plugged)

6. 1/16 Barb Pilot

7. Actuation Relief Vent

Specifications

Compatibility Statement

It is the sole responsibility of the system designer and user to select products suitable for their specific application requirements and to ensure proper installation, operation, and maintenance of these products.

Material compatibility, product ratings and application details should be considered in the selection. Improper selection or use of products described herein can cause personal injury or product damage.



Back