

Miniature Valves:

Toggle, Push-Button & Needle Valves > PUSH BUTTON VALVES > QUICK EXHAUST PUSH BUTTON VALVE 10-32, 1/16" to 1/8" BARB

**QUICK EXHAUST PUSH BUTTON VALVE
10-32, 1/16" to 1/8" BARB**



[larger image](#)

Design Considerations

- The Quick Exhaust Push Button Valves are a compact Normally Closed (Momentary only) design
- 3-Way (Exhausting) 10-32 Female porting
- Air is relieved through three 1/16 diameter exhaust holes in the body
- Supplied with two Electroless Nickel Plated Panel Nuts and lock washer

Example of how to order

<u>Type</u>	<u>Flow Option</u>	<u>Inlet Port</u>	<u>Outlet Port</u>	<u>Seal</u>	<u>Handle</u>
Push Button, Momentary	3-Way (Exhausting), Normally Closed	10-32 Female	10-32 Female	Buna	Black Nylon Button

Part Numbers are a description of the valve as read left to right, Inlet Port to Outlet Port. **QEPB3NC-B,10-32F,W**= Push Button Momentary, 3-Way Exhausting, Normally Closed, Buna Seals, 10-32 Female Inlet x 10-32 Female Outlet, Black Nylon Button

Specifications

Material	BODY and PANEL NUTS - Electroless Nickel Plated Brass, STEM - Brass
Type	Push Button (Momentary)
Flow Option	3-Way (Exhausting)
Seal Option	Buna-N, Ethylene Propylene, Fluoroelastomer (Viton®)
Input Port	10-32 Female, 10-32 Male 1/16 Barb, 3/32 Barb, 1/8 Barb
Output Port ?	10-32 Female, 10-32 Male 1/16 Barb, 3/32 Barb, 1/8 Barb
Spring	STANDARD SPRING - 302 Stainless, 50% SPRING - 302 Stainless
Panel Mount Threads	15/32-32
Maximum Operating Temperature	180 °F
Flow Rate	2.5 SCFM at 50 psi
Toggle Actuation Force - Tested at 50 psi	Detented Standard Spring - 9 oz Momentary Standard Spring - 1 lb 3 oz
Compatibility Statement	It is the sole responsibility of the system designer and user to select products suitable for their specific application requirements and to ensure proper installation, operation, and maintenance of these products. Material compatibility, product ratings and application details should be considered in the selection. Improper selection or use of products described herein can cause personal injury or product damage.
	Our Minimum Order Requirements are \$100.00 Domestic - \$250.00 International.

Pricing and Minimum Order Requirement

Pricing is based on the quantity ordered.
Please indicate a typical order quantity or Estimated Annual Usage when requesting pricing.

[Print](#)

[Back](#)
