

THE SPECIALTY MFG. CO.

5858 Centerville Road St. Paul, MN 55127 **SMC** will quote alternate materials or customize our standard products when quantities ensure competitive pricing. **Contact Customer Service** at (651) 653-0599

FAX - (651) 653-0989 E-Mail - info@specialtymfg.com

SIDE PORT NEEDLE VALVE 10-32, 1/16" to 1/8" BARB



Design Considerations

- The Side Port Needle Valves are a compact 10-32 Female design
- 6.5 Turn Adjustment Needle
- Smooth or Ribbed Knob in Black or Gray ABS
- Supplied with two Electroless Nickel Plated Panel Nuts and lock washer
- * * * * Knobs are Optional * * *

Example of now to order						
Type	Seal	Needle	Inlet Port	Outlet Port	Knob	
Needle Valve	Buna	6.5 Turn	10-32	10-32	Ribbed Black	
			Female	Female	ABS	

Part Numbers are a description of the valve as read left to right, Inlet Port to Outlet Port. SPNV2SV-B,6.5T,10-32F,10-32F,RB = Needle Valve, Buna Seals,6.5 Turn Needle, 10-32 Female Inlet x 10-32 Female Outlet, Ribbed Black ABS Knob

Specifications

Material	BODY and PANEL NUTS - Electroless Nickel Plated Brass		
Seal Option	Buna-N, Ethylene Propylene, Fluoroelastomer (Viton®)		
Needle Option	6.5 Turn Brass		
Input Port	10-32 Female, 10-32 Male 1/16 Barb, 3/32 Barb, 1/8 Barb		
Output Port	10-32 Female, 10-32 Male 1/16 Barb, 3/32 Barb, 1/8 Barb		
Knob	Smooth Black ABS, Smooth Gray ABS Ribbed Black ABS, Ribbed Gray ABS		
Panel Mount Hole	0.500 in		
Maximum Panel Thickness	0.250 in		
Panel Mount Threads	15/32-32		
Maximum Operating Pressure	0 to 125 psi		
Maximum Operating Temperature	180 °F		
Flow Rate	2.5 SCFM at 50 psi		
Compatibility Statement	It is the sole responsibility of the system designer and user to select products suitable for their specific application requirements and to ensure proper installation, operation, and maintenance of these products. Material compatibility, product ratings and application details should be considered in the selection. Improper selection or use of products described herein can cause personal injury or product		

	damage.
Pricing and Minimum Order Requirement	Our Minimum Order Requirements are \$100.00 Domestic - \$250.00 International. Pricing is based on the quantity ordered. Please indicate a typical order quantity or Estimated Annual Usage when requesting pricing.