

Miniature Valves:

Toggle, Push-Button & Needle Valves > PUSH BUTTON VALVES > SWIVEL PUSH BUTTON VALVE 10-32, 1/16" to 1/8" BARB

**SWIVEL PUSH BUTTON VALVE
10-32, 1/16" to 1/8" BARB**



[larger image](#)

Design Considerations

- Swivel Push Button Valves are a compact Normally Closed (Momentary only) design
- 10-32 Swivel Body for easy orientation after installation
- 2-Way (Non-Exhausting) or 3-Way (Exhausting)
- The 3-Way (Exhausting) Push Button Valves relieve air around the push button
- Supplied with two Electroless Nickel Plated Panel Nuts and lock washer

Example of how to order

<u>Type</u>	<u>Flow Option</u>	<u>Seal</u>	<u>Inlet Port</u>	<u>Outlet Port</u>	<u>Handle</u>
Push Button, Momentary	2-Way (Non-Exhausting), Normally Closed	Buna	10-32 Female	10-32 Female	Black Nylon

Part Numbers are a description of the valve as read left to right, Inlet Port to Outlet Port.
SWPB2NC-B,10-32F,B = Swivel Push Button Momentary, 2-Way Non-Exhausting, Normally Closed, Buna Seals, 10-32 Female Inlet x 10-32 Female Outlet, Black Nylon Button

Specifications

Material	BODY and PANEL NUTS - Electroless Nickel Plated Brass, STEM - Brass
Type	Push Button (Momentary)
Flow Option	2-Way (Non-Exhausting) Normally Closed, 3-Way (Exhausting) Normally Closed
Seal Option	Buna-N, Ethylene Propylene, Fluoroelastomer (Viton®)
Input Port	10-32 Female, 10-32 Male 1/16 Barb, 3/32 Barb, 1/8 Barb
Output Port ?	10-32 Female, 10-32 Male 1/16 Barb, 3/32 Barb, 1/8 Barb
Push Button Style & Color	Black Nylon, Gray Nylon, Light Gray Nylon, White Nylon, Blue Nylon, Red Nylon New Style Black Nylon Black Delrin Ball Electroless Nickel Plated Brass
Spring	STANDARD SPRING - 302 Stainless, 50% SPRING - 302 Stainless
Panel Mount Threads	15/32-32
Maximum Operating Temperature	180 °F
Flow Rate	2.5 SCFM at 50 psi
Compatibility Statement	It is the sole responsibility of the system designer and user to select products suitable for their specific application requirements and to ensure proper installation, operation, and maintenance of these products. Material compatibility, product ratings and application details should be considered in the selection. Improper selection or use of products described herein can cause personal injury or

	product damage.
Pricing and Minimum Order Requirement	<p>Our Minimum Order Requirements are \$100.00 Domestic - \$250.00 International. Pricing is based on the quantity ordered. Please indicate a typical order quantity or Estimated Annual Usage when requesting pricing.</p>

[Print](#)

[Back](#)