Miniature Valves:

<u>Toggle, Push-Button & Needle Valves</u> > <u>TOGGLE VALVES</u> > SWIVEL TOGGLE VALVE (Female x Female) 1/8" NPT

SWIVEL TOGGLE VALVE (Female x Female) 1/8" NPT



larger image

Design Considerations

- The Swivel Toggle Valves are a compact Normally Closed design
- Detented or Momentary Toggle Handle
- 1/8 NPT Swivel Body for easy orienation after installation
- 2-Way (Non-Exhausting) or 3-Way (Exhausting)
- The 3-Way (Exhausting) Toggle Valves relieve air around the handle

Example of how to order

<u>Type</u>	Flow Option	<u>Seal</u>	Inlet Port	Outlet Port	<u>Handle</u>
Toggle Activated,	3-Way	Buna	1/8 FNPT	1/8 FNPT	Black Nylon
Detented	(Exhausting),				
	Normally				
	Closed				

Part Numbers are a description of the valve as read left to right, Inlet Port to Outlet Port.

SWTA3NC-B,1/8F,B,NPM =Swivel Body, Toggle Activated Detented, 3-Way Exhausting, Normally Closed, Buna Seals, 1/8 Female NPT Inlet x 1/8 Female NPT Outlet, Black Nylon Toggle Handle

Specifications

Material	BODY - Electroless Nickel Plated Brass, STEM - Brass		
Туре	Toggle Activated (Detented), Toggle Momentary (Spring Return)		
Flow Option	2-Way (Non-Exhausting) Normally Closed, 3-Way (Exhausting) Normally Closed		
Seal Option	Buna-N, Ethylene Propylene, Fluoroelastomer (Viton®)		
Input Port	1/8 Female NPT		
Output Port	1/8 Female NPT		
Toggle Style and Color	Black Nylon, Gray Nylon, Light Gray Nylon Electroless Nickel Plated Brass, Short Electroless Nickel Plated Brass		
Spring	STANDARD SPRING - 302 Stainless, 50% SPRING - 302 Stainless		
Maximum Operating Temperature	180 °F		
Flow Rate	2.5 SCFM at 50 psi		
Toggle Actuation Force - Tested at 50 psi	Detented Standard Spring - 9 oz Momentary Standard Spring - 1 lb 3 oz		
Compatibility Statement	It is the sole responsibility of the system designer and user to select products suitable for their specific application requirements and to ensure proper installation, operation, and maintenance of these products. Material compatibility, product ratings and application details should be considered in the selection. Improper selection or use of products described herein can cause personal injury or product damage.		

	Our Minimum Order Requirements are \$100.00 Domestic - \$250.00 International.		
Pricing and Minimum Order	Pricing is based on the quantity ordered.		
Requirement	Please indicate a typical order quantity or Estimated Annual Usage when requesting		
	pricing.		

Print Back