



THE SPECIALTY MFG. CO.
5858 Centerville Road
St. Paul, MN 55127

SMC will quote alternate materials or customize our standard products when quantities ensure competitive pricing.
Contact Customer Service at (651) 653-0599
FAX - (651) 653-0989
E-Mail - info@specialtymfg.com

MALE QUICK DISCONNECT (With Valve) 10-32 FEMALE



Design Considerations

- Male Quick Disconnect
- With built in shutoff valve
- Automatically stops flow when disconnected

Example of how to order

<u>Type</u>	<u>Body</u>	<u>End Option</u>
Male Quick Disconnect	With Valve	10-32 Female

Part Numbers are a description of the valve as read left to right, Inlet Port to Outlet Port.

QD MALE,W/VALVE,10-32F= Male Quick Disconnect, With Valve, 10-32 Female




Compatibility Statement:

It is the sole responsibility of the system designer and user to select products suitable for their specific application requirements and to ensure proper installation, operation, and maintenance of these products. Material compatibility, product ratings and application details should be considered in the selection. Improper selection or use of products described herein can cause personal injury or product damage.

Pricing and Minimum Order Requirement:

Our Minimum Order Requirements are \$100.00 Domestic - \$250.00 International. Pricing is based on the quantity ordered. **Please indicate a typical order quantity or Estimated Annual Usage when requesting pricing.**

Results 1 - 5 of 5

Item #	Image	Body	End Option	Maximum Operating Pressure	Maximum Operating Temperature
QD MALE,W/VALVE,10-32F	 QD MALE,W/VALVE,10-32F larger image	QD MALE,W/VALVE	10-32 Female	125 psi	180 °F
QD MALE,W/VALVE,10-32M	 QD MALE,W/VALVE,10-32M larger image	QD MALE,W/VALVE	10-32 Male	125 psi	180 °F
QD MALE,W/VALVE,1/16B	 QD MALE,W/VALVE,1/16B	QD MALE,W/VALVE	1/16 Barb	125 psi	180 °F

larger image



QD
MALE, W/VALVE, 3/32B

QD
MALE, W/VALVE, 3-
32B

QD
MALE, W/VALVE

3/32 Barb

125 psi

180 °F

larger image



QD
MALE, W/VALVE, 1/8B

QD
MALE, W/VALVE, 1/8B

QD
MALE, W/VALVE

1/8 Barb

125 psi

180 °F

larger image

Results 1 - 5 of 5