## THE SPECIALTY MFG. CO.

5858 Centerville Road St. Paul, MN 55 I 27 Custom Is Our Specialty ISO 9001:2015 MADE IN THE USA The Specialty Mfg. Co. will quote alternate materials or customize our standard products when quantities ensure competitive pricing. Contact Customer Service at (651) 653-0599 FAX - (651) 653-0989 E-Mail - info@specialtymfg.com

## 10-32 MALE MINI NEEDLE VALVE 10-32, 1/16" to 1/8" BARB



## Design Considerations

- The 10-32 Male Mini Needle Valves are a compact 10-32 Male x 10-32 Female Design
- 5 Turn Adjustment Needle
- Small Knurled Knob
- Supplied with two Electroless Nickel Plated Panel Nuts and lock washer

Example of how to order						
<u>Type</u> Needle Valve	<u>Seal</u> Buna	<u>Needle</u> 5 Turn	<u>Inlet Port</u> 10-32 Male	<u>Outlet Port</u> 1/8 Barb	<u>Knob</u> Small Knurled Knob	

Part Numbers are a description of the valve as read left to right, Inlet Port to Outlet Port. MNV2SV-B,10-32M,1/8B = Mini Needle Valve, Buna Seals, 5 Turn Needle, 10-32 Male Inlet x 1/8 Barb Outlet, Small Knurled Knob

## Specifications

Material	BODY, PANEL NUTS and STEM - Electroless Nickel Plated Brass			
Seal Option	Buna-N, Ethylene Propylene, Fluoroelastomer (Viton®)			
Needle Option	5 Turn Brass			
Input Port	10-32 Male			
Output Port	10-32 Female, 10-32 Male 1/16 Barb, 3/32 Barb, 1/8 Barb			
Knob	Small Knurled Knob			
Panel Mount Hole	0.500 in			
Maximum Panel Thickness	0.250 in			
Panel Mount Threads	15/32-32			
Maximum Operating Pressure	0 to 125 psi			
Maximum Operating Temperature	180 °F			
Flow Rate	2.5 SCFM at 50 psi			
Compatibility Statement	It is the sole responsibility of the system designer and user to select products suitable for their specific application requirements and to ensure proper installation, operation, and maintenance of these products. Material compatibility, product ratings and application details should be considered in the selection Improper selection or use of products described herein can cause personal injury or product damage.			
Pricing and Minimum Order Requirement	Our Minimum Order Requirements are \$150.00 Domestic - \$250.00 International. Pricing is based on the quantity ordered. Please indicate a typical order quantity or Estimated Annual Usage when requesting pricing.			