

THE SPECIALTY MFG. CO.

Custom Is Our Specialty

5858 Centerville Road
St. Paul, MN 55127

ISO 9001:2015
MADE IN THE USA

The Specialty Mfg. Co. will quote alternate materials or customize our standard products when quantities ensure competitive pricing.
Contact Customer Service at (651) 653-0599
FAX - (651) 653-0989
E-Mail - info@specialtymfg.com

SINGLE SHUTOFFS 3/4" GARDEN HOSE



Design Considerations

- Shutoffs are inexpensive Female Garden Hose to Male Garden Hose valves designed for outdoor use
- Shutoffs are designed for city water pressure to a maximum of 80 psi
- Shutoffs are a one way valve and require approximately 20 psi of water pressure to seal in the closed position
- An optional Zero Pressure Washer is available for #35 Shutoff applications with less than 20 psi of working line pressure
- Custom Colors are available for orders of 30,000 or more
- The #45 Swivel Shutoff incorporates a Swivel Female Garden Hose Inlet End

Example of how to order

<u>Type</u>	<u>Color</u>	<u>Washer</u>
Single Shutoff	Yellow	Garden Hose Washer

Part Numbers are a description of the Shutoff.

#35 SHUTOFF, YELLOW = Yellow ABS Single Shutoff, 3/4 Female Garden Hose Inlet x 3/4 Male Garden Hose Outlet, Buna Seals, Black ABS Handle, Garden Hose Washer

Specifications

Body Type	#35 Single Shutoff #45S Swivel Shutoff
Material	ABS - Black ABS - Blue ABS - Green ABS - White ABS - Yellow Black Glass Filled Polypropylene White Glass Filled Polypropylene
Flow Type	All Shutoffs - Flow from Female to Male
Handle Option	Black ABS Handle and Ball
Seal Option	Buna-N
Washer Option	GARDEN HOSE WASHER - Requires 20 psi to Seal ZERO PRESSURE WASHER - Requires less than 20psi to Seal
Maximum Operating Pressure	80 psi
Maximum Operating Temperature	125 °F
Ball Through Hole Diameter	0.437 in
Compatibility Statement	It is the sole responsibility of the system designer and user to select products suitable for their specific application requirements and to ensure proper installation, operation, and maintenance of these products. Material compatibility, product ratings and application details should be considered in the selection. Improper selection or use of products described herein can cause personal injury or product damage.

Pricing and Minimum Order Requirement

Our Minimum Order Requirements are \$11 0.00 Domestic - \$250.00 International.
Pricing is based on the quantity ordered.
Please indicate a typical order quantity or Estimated Annual Usage when requesting pricing.