## THE SPECIALTY MFG. CO.

5858 Centerville Road St. Paul, MN 55127 Custom Is Our Specialty
ISO 9001:2015
MADE IN THE USA

The Specialty Mfg. Co. will quote alternate materials or customize our standard products when quantities ensure competitive pricing. Contact Customer Service at (651) 653-0599 FAX - (651) 653-0989 E-Mail - info@specialtymfg.com

## 1200 SERIES POPPET CHECK VALVE

Click here to design your valve in 3D using our online configurator.



## **Design Considerations**

- Incorporates an o-ring captured in a brass poppet to seal on a brass seat in valve body
- Maximum operating pressure is 1200 psi
- Economical, general use design that provides positive seal down to approx. 1/2 psi back pressure
- UL / UR configurations are available and rated to 500 psi

## Order Example:

<u>Material</u>	Inlet Port	<b>Outlet Port</b>	<u>Seal</u>	<u>Spring</u>
Brass	3/4 MNPT	3/4 MNPT	Viton®	1 psi

**Part Numbers** are a description of the valve as read left to right, Inlet to Outlet.

**CHK BRS 1200-12M12M-F,1#** = Brass Check Valve, 3/4 Male NPT Inlet x 3/4 Male NPT Outlet, Viton ® Seals, 1 psi Spring

Material Option	BODY, POPPET and STOP – Brass	
Plating Option	No Plating, Electroless Nickel Plating	
Body Option	3/4 MNPT Inlet x 3/4 MNPT Outlet	
Seal Option	Buna-N, Ethylene Propylene, Fluoroelastomer (Viton®), Neoprene	
Spring Option:	302 Stainless Spring – 1 psi, 3 psi, 5 psi	
Material - Cracking Pressure	No Spring	
Cv Value	Varies, contact us to discuss	
Full Port	0.470 in	
Maximum Operating Pressure	1200 psi	
Temperature Range	*** NOT RATED FOR STEAM ***	
	Buna-N -35°F to +250°F Ethylene Propylene (EPDM) -65°F to +300°F Fluoroelastomer (Viton®) -15°F to +400°F Neoprene -35°F to +250°F	
Compatibility Statement	It is the sole responsibility of the system designer and user to select products suitable for their specific application requirements and to ensure proper installation, operation, and maintenance of these products. Material compatibility, product ratings and application details should be considered in the selection. Improper selection or use of products described herein can cause personal injury or product damage.	
Pricing and Minimum Order Requirement	Our Minimum Order Requirements are \$150.00 Domestic - \$250.00 International. Pricing is based on the quantity ordered. Please indicate a typical order quantity or Estimated Annual Usage when requesting pricing.	