

## M92 SERIES SWIVEL

1/8" to 1/4" NPT, 5/16 BARB

### Design Considerations

- 5/16 Hose Barb Swivel
- 1/4 HEX Drive - NPT Steel Post with Brass Barb Body
- Available with Buna-N, EP or Viton® Seals



SCAN ME  
your exact valve

### Specifications:

Item #	Description	Image	End Option	Body	Seal Option	Overall Length	Maximum Operating Pressure	Maximum Operating Temperature
M92-2M5B B,1.25	1/4 Hex Drive 90 Degree Swivel		1/8 Male NPT	5/16 Barb	Buna-N	1.25 in	250 psi	180 °F
M92-2M5B B,2.0	1/4 Hex Drive 90 Degree Swivel		1/8 Male NPT	5/16 Barb	Buna-N	2.0 in	250 psi	180 °F
M92-4M5B B,2.13	1/4 Hex Drive 90 Degree Swivel		1/4 Male NPT	5/16 Barb	Buna-N	2.13 in	250 psi	180 °F
M92-2M5B E,1.25	1/4 Hex Drive 90 Degree Swivel		1/8 Male NPT	5/16 Barb	Ethylene Propylene (EPDM)	1.25 in	250 psi	180 °F
M92-2M5B E,2.0	1/4 Hex Drive 90 Degree Swivel		1/8 Male NPT	5/16 Barb	Ethylene Propylene (EPDM)	2.0 in	250 psi	180 °F
M92-4M5B E,2.13	1/4 Hex Drive 90 Degree Swivel		1/4 Male NPT	5/16 Barb	Ethylene Propylene (EPDM)	2.13 in	250 psi	180 °F
M92-2M5B F,1.25	1/4 Hex Drive 90 Degree Swivel		1/8 Male NPT	5/16 Barb	Fluoroelastomer (Viton®)	1.25 in	250 psi	180 °F
M92-2M5BF,2.0	1/4 Hex Drive 90 Degree Swivel		1/8 Male NPT	5/16 Barb	Fluoroelastomer (Viton®)	2.0 in	250 psi	180 °F
M92-4M5BF, 2.13	1/4 Hex Drive 90 Degree Swivel		1/4 Male NPT	5/16 Barb	Fluoroelastomer (Viton®)	2.13 in	250 psi	180 °F

### Example of how to order:

Type	End Option	Body	Seal	Overall Length
90 Degree Swivel	1/8 MNPT	5/16 Barb	Viton®	1.25"

**Part Numbers** are a description of the swivel as read left to right, Inlet Port to Outlet Port  
**M92-2M5B-F,1.25** = 90 Degree Swivel, 1/8 Male NPT x 5/16 Barb, Viton® Seals, 1/4 HEX x 1.25" Post