

Male Quick Disconnect (with valve)



Design Consideration




- Male Quick Disconnect
- With built in shutoff valve
- Automatically stops flow when disconnected


Example of how to order

Type: Male Quick Disconnect **Body:** With Valve **End Option:** 10-32 Female

Part Numbers are a description of the valve as read left to right, Inlet Port to Outlet Port.

QD MALE,W/VALVE,10-32F= Male Quick Disconnect, With Valve, 10-32 Female

Item #	Image	Body	End Option	Maximum Operating Pressure	Maximum Operating Temperature
QD MALE,W/VALVE,10-32F	 QD MALE,W/VALVE,10-32F larger image	QD MALE,W/VALVE	10-32 Female	125 psi	180 °F
QD MALE,W/VALVE,10-32M	 QD MALE,W/VALVE,10-32M larger image	QD MALE,W/VALVE	10-32 Male	125 psi	180 °F
QD MALE,W/VALVE,1/16B	 QD MALE,W/VALVE,1/16B	QD MALE,W/VALVE	1/16 Barb	125 psi	180 °F

Item #	Image	Body	End Option	Maximum Operating Pressure	Maximum Operating Temperature
QD MALE, W/VALVE, 3/32B	 <p>QD MALE, W/VALVE, 3- 32B larger image</p>	QD MALE, W/VALVE	3/32 Barb	125 psi	180 °F
QD MALE, W/VALVE, 1/8B	 <p>QD MALE, W/VALVE, 1/8B larger image</p>	QD MALE, W/VALVE	1/8 Barb	125 psi	180 °F